



**Table of Contents**

**Table of Contents**.....2

**1. Schematic, BOM List and PCB Layout** .....3

    1.1 Schematic .....3

    1.2 BOM List .....3

    1.3 PCB Layout.....4

**2. Efficiency** .....5

**3. Load Regulation** .....5

**4. Line Regulation** .....6

**5. Output Voltage Ripple**.....7

**6. VIN Power On/Off**.....7

**7. EN On/Off** .....8

**8. Load Transient**.....9

**9. Line Transient**.....9

**10. SCP Entry and Recovery** .....10

**11. VIN/EN On/Off during SCP**.....11


**12. OTP Entry**.....11

**13. Thermal Test**.....12

SGMICRO CONFIDENTIAL

1. Schematic, BOM List and PCB Layout


1.1 Schematic



1.2 BOM List


Item	Quantity	Designator	Description	Manufactory
1	2	C1,C13	Ceramic capacitor, 0.1µF 25V, X7R, ±10%, 0603	muRata
2	1	C2	Ceramic capacitor, 4.7µF 25V, X5R, ±10%, 0805, GRM219R61E475KA73	muRata
3	3	C3,C4,C5	Ceramic capacitor, 47µF 10V, X7R, ±10%, 1210, GRM32ER71A476KE15	muRata
4	0	C6	NC	/
5	1	C7	Solid Electrolytic capacitor, 100µF, 35V	Standard
6	1	C8	Ceramic capacitor, 10µF 25V, X7R, ±10%, 1210, GCM32ER71E106KA57	muRata
7	1	C9	Ceramic capacitor, 4.7µF 50V, X7R, ±10%, 1210, GCJ32ER71H475KA12	muRata
8	2	C10,C11	Ceramic capacitor, 15nF 50V, X7R, ±10%, 0603	muRata
9	1	C12	Ceramic capacitor, 22pF 50V, C0G, ±5%, 0603	muRata
10	1	L1	Ind., 3.3µH±20%, ITEMP(40°C)=18.2A, ISAT(30%)=24.7A, DCR=5.2mΩ, 7443320330	Würth
11	2	R1,R7	Film Resistor, 1%, 0Ω, 0603	Standard
12	1	R2	Film Resistor, 1%, 56KΩ, 0603	Standard
13	1	R3	Film Resistor, 1%, 10KΩ, 0603	Standard
14	0	R4,R5	NC	/
15	1	R6	Film Resistor, 1%, 100KΩ, 0603	Standard
16	1	R8	Film Resistor, 1%, 3.24KΩ, 0603	Standard
17	1	R9	Film Resistor, 1%, 10.5KΩ, 0603	Standard
18	1	R10	Film Resistor, 1%, 2.8KΩ, 0603	Standard
19	1	U1	SGM61164, 6A, 18V, Synchronous Buck Converter, TQFN-3.5×3.5-14L	SGMICRO
				<b>Conclusion: Total 22 components</b>

1.3 PCB Layout




### 2. Efficiency

Test conditions:  $V_{IN}=5.5V/12V$ ,  $V_{OUT}=3.3V$ , EN floating.




### 3. Load Regulation

Test conditions:  $V_{IN}=5.5V/12V$ ,  $V_{OUT}=3.3V$ , EN floating.



4. Line Regulation





Test conditions:  $V_{OUT}=3.3V$ ,  $I_{OUT}= 0.1A/3A/6A$ , EN floating.



SGMICRO CONFIDENTIAL



### 5. Output Voltage Ripple

Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ .





### 6. VIN Power On/Off

Test conditions:  $V_{OUT}=3.3V$ ,  $I_{OUT}=0A$ .





Test conditions:  $V_{OUT}=3.3V$ ,  $I_{OUT}=6A$ .





### 7. EN On/Off

Test conditions:  $V_{OUT}=3.3V$ ,  $I_{OUT}=0A$ .




Test conditions:  $V_{OUT}=3.3V$ ,  $R_{LOAD}=0.55\Omega$ .




### 8. Load Transient

Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ , Slew rate= $0.5A/\mu s$ .

$I_{OUT}=50mA$  to  $3A$  to  $50mA$




$I_{OUT}=3A$  to  $6A$  to  $3A$




Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ , Slew rate= $4A/\mu s$ .

$I_{OUT}=50mA$  to  $3A$  to  $50mA$




$I_{OUT}=3A$  to  $6A$  to  $3A$




### 9. Line Transient



Test conditions:  $V_{OUT}=3.3V$ ,  $I_{OUT}=3A$ , EN floating.

$V_{IN}=5V$  to  $12V$





$V_{IN}=12V$  to  $5V$







10. SCP Entry and Recovery

Test conditions: V<sub>IN</sub>=12V, V<sub>OUT</sub>=3.3V, I<sub>OUT</sub>=0A, Output Shorted Protection.







Test conditions: V<sub>IN</sub>=12V, V<sub>OUT</sub>=3.3V, I<sub>OUT</sub>=6A, Output Shorted Protection.




11. VIN/EN On/Off during SCP

Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ , Output Shorted.




12. OTP Entry

Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ ,  $R_{LOAD}=1\Omega$ , Over temperature Protection.



13. Thermal Test

Test conditions:  $V_{IN}=12V$ ,  $V_{OUT}=3.3V$ , Room temperature test, Natural air convection heat dissipation.



$I_{OUT}(A)$	1.5	3	4.5	6	7.2
IC Top Case(°C)	40.4	51.9	71.1	98.0	133.7
Inductor(°C)	33.1	37.1	43.7	51.7	63.4
PCB(°C)	30.7	33.0	36.9	41.5	49.3
Ambient(°C)	28.1	28.2	28.4	28.0	28.2